

September 2020
Version 01

6880 SubliColor Impact II 120

Dye sublimation transfer paper 120 g/m² for hard substrates

APPLICATIONS

- Specifically developed for the sublimation transfer of high-resolution photos and images to hard substrates, i.e. coated sheets of metal, wood or table tops, mugs, etc...

FEATURES

- Compatible with Epson, Ricoh and Sawgrass small format printers
- Instant dry
- High quality printing and high optical densities
- Very high transfer rates and smooth release
- Very good stability of sheets
- Porosity > 100ml/min

PHYSICAL PROPERTIES

| Grammage | Thickness | Opacity |
|----------------------|-----------|---------|
| 120 g/m ² | 143 µm | > 90 % |

PRESENTATION

| Sizes | Packaging | Units per pallets | Core |
|-----------------|------------------|-------------------|--------------|
| 432 mm x 40m | 1 | 36 | 2" |
| 610 mm x 40m | 1 | 36 | 2" |
| 432 mm x 80m | 2 | 70 | 3" |
| 610 mm x 80m | 1 | 35 | 3" |
| 1118 mm x 80 m | 1 | 35 | 3" |
| 1620 mm x 120 m | 1 | 20 | 3" |
| A4 / A3 | 100 sheets / box | 8000 / 3000 | MOQ 10 boxes |

COMPATIBILITIES

Technologies
- Piezo

Encres- Inks

Water-based dye
sublimation inks