
















SOFT METALLIC HEAT TRANSFER MATERIAL FEATURES A DISTINCT LUSTER AND SHINE

Creates a soft, metallised finish for textile decoration. It is supplied on a self-adhesive polyester carrier



AVAILABLE IN

50 cm x 10 m rolls

RECOMMENDED FABRICS

- 100% cotton
- 100% polyester
- · Polyester-cotton blends blends
- * Test before application!

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For opti-mal cutting and weeding, maintain a line thickness of at least 1.5 mm (1/16") for lettering and logos.

APPLICATION INSTRUCTIONS

Temperature: 150° C Time: 10 sec. Pressure: medium (#4-6 bei Hotronix®)

Peel: cold

MULTI-COLOR DESIGNS

Apply background for 2-4 seconds, peel carrier warm/cold. Repeat for additional colors. Finish with final application of 13-15 seconds. Peel cold.

ACCESSORIES RECOMMENDED

- · Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry-clean. Do not iron directly onto CAD-CUT® Soft Metallic (use cover sheet).

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS





Easy weed



Ironable



Ironable only



inside out Washable



Sublimation



Stretchable



Flock





Thin



Multi-color application



Peel hot



Application



Pressure

CAD-CUT® SOFT METALLIC

