

EasyColor™

Direct to Vinyl (DTV™)

SPECIFICATIONS

Composition	Average Thickness	© Carrier			
	100 microns	non adhesive	REACH n° 1907/2006/EU		
PU			OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 22.HIT:05027 HOHENSTEIN HTTI		

APPLICATION INSTRUCTIONS

⊘ Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/ cotton blends, elastan (not suited for treated	Blade	<u></u> Pressure	>> Speed	Time	Temperature	Pressure	Peel
and dye sublimated textiles)	45°	50 gf	20 cm/sec	15 seconds	155°C (311°F)	Medium (2,5/3,5 bar)	warm

- → Print, cut and peel off excess material
- → Remove the print by hand or with the help of TTD Advanced
- → Without TTD = preheat the underplaten for 5 sec. / 155°C.*
- → Place the decoration on the garment (*without TTD > cover with parchment paper)
- ightarrow Apply following the recommended parameters and remove the TTD/parchment-paper warm

For CRAFT:

- → Let the print dry for 5 minutes.
- → Silhoutte settings: blade 3, force 3, speed 8. Cricut settings: Everyday iron on
- → Home iron: "silk" setting & cover the transfer with parchment-paper & iron for 90 seconds (for an A5)
- → Remove the parchment-paper warm

PRODUCT HIGHLIGHTS

- →One-piece designs do not need an application-tape
- → Suitable for nearly all common ink-jet-systems
- → Variable finish matte or glossy depending on parchment-paper or teflonsheet
- → Very fast to weed

NOTE: Given the large number of inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Ony cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	∮ ⊳ Position
Up to 40°C best inside-out	YES best inside-out	YES (synthetic cycle)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- → Wait 24 hours after the application before the first wash
- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com
For further information, please contact our sales office: info@siser.it



Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it www.siser.com r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246





