

# **Vipond's Paints Pty Ltd**

58 Barrie Road, Tullamarine VIC 3043 Phone (03)9350 4188 Email info@viponds.com.au

www.viponds.com.au

#### PRODUCT INFORMATION

## **FLUORESCENT PAINT**

### Description

A water thinned acrylic paint using the highest quality pigment available for colour brightness and colour retention. Fluorescent paint is inherently transparent which allows light to travel through the paint film and then re-emit light of its own colour, under "black light" it glows very brightly. To enable this to happen it must be applied over a white background. Due to this characteristic fluorescent paint has poor light stability and will begin to fade within 6 months when subjected to direct sunlight.

#### Use

It is primarily used for signwriting windows and buildings, where the brilliance of fluorescent colour is required. When painting vinyl banners use Tautflex Fluorescent

## **Application**

Thoroughly stir and apply by brush, roller or spray. Apply evenly for best results with at least 2 coats for coverage and durability.

#### **Surface Preparation**

Thoroughly clean the surface. Then apply Viponds Background White. Use Vipond's Tautflex White for banner applications. It **must** be applied over a white background.

## **Drying**

Under normal drying conditions (above 15°C and low humidity) it is touch dry within 30 minutes and can be recoated after 2 hours.

#### Cleaning up and thinning

Use clean water only

### Coverage

Approximately 10- 12 square metres per litre per coat

#### Pack Size

200ml, 500 ml, 1 litre, 4 litre.

#### **Colours**

White/clear, yellow, green, pink, red, orange, blue,

Revised January 2021