

Avery Dennison® MPI1106

Opaque Hi Tack Easy Apply™

Revision: 3 Dated: 11/13/19

Uses:

Avery Dennison® MPI1106 Hi Tack Easy Apply gloss premium cast film is an opaque solid color, conformable vinyl film designed for use in demanding applications. The adhesive system is designed for use on low energy substrates such as plastics, powder coat paints, fiberglass, clear coats and painted metal surfaces. This product is ideal for a variety of outdoor projects. Reference performance guarantee for coverage. Graphics can be overlaminated or clear coated with a UV screen print clear. Reference ICS Documentation for coverage.



Face: 2.0 mil (51 microns) high gloss cast film



Adhesive: Clear High Performance Acrylic



Liner: 90# Easy Apply™

Application Surfaces:

Flat, Simple Curves, Complex Curves

Features:

- Excellent for OEM durable decal applications
- Outstanding durability and outdoor performance
- Good UV, temperature, humidity, and salt-spray resistance
- High performance adhesive for difficult substrates
- Dimensionally stable liner for easy converting
- Air egress technology for bubble free application
- ICC profiles available on the Avery Dennison's website (<http://avery-us.color-base.com>)

Conversion:

- Latex Inkjet
- Solvent Based Inkjet
- Mild/Eco Solvent Inkjet
- UV Inkjet*

* For flat surfaces only, except for qualified flexible UV inks

Common Applications:

- Heavy Equipment
- Trucks and Trailers
- Buses and Transit
- Rail Car
- Commuter Rail
- Snow Vehicles
- ATV / Recreational Vehicles

Product Data Sheet

Page 1 of 4



Graphics Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI1106

Opaque Hi Tack Easy Apply™

Revision: 3 Dated: 11/13/19

Physical Characteristics:

Property	Measurement	Typical Value
Caliper, face		2.0 mil (51µm)
Caliper, adhesive		1.0 mil (25 µm)
Dimensional stability		<0.015" (0.4mm) Note: Ink loads in excess of 250% may cause increased shrinkage and/or increased initial adhesion of the printed film
Tensile at Yield		4.0 - 8.0 lb/in (0.7–1.5 kg/cm)
Elongation		200% min.
Gloss	Hunter Gloss @ 60 degrees	90 GU
Adhesion:	<p>LSE Plastics LSE Clearcoats LSE Paints LSE Textured Substrates</p> <p>Stainless Steel</p>	<p>4.1 lbs/in (718 N/m) 4.3 lbs/in (753 N/m) 4.5 lbs/in (788 N/m) 3.5 lbs/in (613 N/m)</p> <p>5.5 lbs/in (963 N/m)</p> <p>LSE – Low Surface Energy</p>
Flammability	ASTM E-84	Self Extinguishing Class 1 or A rating
Shelf-Life		2 years from the date of manufacture (when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.)
Durability	Vertical Exposure	up to 7 years – see ICS Performance Guarantee for printed durability
Min. Application Temperature		40° F (4° C) Flat
Service Temperature		-40° to 180°F (-40° to 82° C) (Reasonable range of temperatures which would be expected under normal environmental conditions).
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions
Compliance		California Proposition 65

Product Data Sheet

Page 2 of 4



Graphics Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI1106

Opaque Hi Tack Easy Apply™

Revision: 3 Dated: 11/13/19

Data represents average values where applicable, and is not intended for specification purposes.

Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery.. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

▲ WARNING

Failure to install the film in full compliance with Avery Dennison's installation instructions may result in personal injury or property damage. Read and follow all instructions when installing the film.

Product Data Sheet

Page 3 of 4



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379

Avery Dennison® MPI1106

Opaque Hi Tack Easy Apply™

Revision: 3 Dated: 11/13/19

Related Documents:

The following Avery Dennison literature will provide complete information to the user for proper application, storage, and other requirements and is available upon request from your Avery Dennison representative or from the Avery Dennison website (www.graphics.averydennison.com).

Document Title	Reference Number
Substrate Cleaning and Preparation	Instructional Bulletin #1.10
Storage, Maintenance, and Cleaning of PVC Films	Instructional Bulletin #1.20
Warranty of Avery Dennison Films	Instructional Bulletin #1.30
Multi Purpose Ink Jet OEM Qualification Matrix, Durability Reference, & Troubleshooting Guide	Instructional Bulletin #5.80
Premask Recommendations	Instructional Bulletin #5.50

Revisions are italicized

Avery Dennison® is a registered trademark of Avery Dennison Corporation
Easy Apply™ is a trademark of Avery Dennison Corporation

Product Data Sheet

Page 4 of 4



Graphics
Solutions

www.graphics.averydennison.com
Customer Service: 800-282-8379