

## Product Information

Application Tape based on a transparent PVC film with silicone paper liner as a protective cover.

Suitable for transferring self adhesive signs, logos and lettering which are produced manually or with CAD/CAM plotter.

Especially to be emphasised are the following properties:

- The silicone paper liner, on the back side printed with blue squares, improves the cutting of the film.
- Finished lettering which are applied by the Application Tape can be covered with the silicone paper liner as protection during an intermediate storing or a long-term shipment.
- The acrylic adhesive offers a high and immediate adhesion which will not considerably change, even after a long storage.

## Technical Data

<b>Carrier:</b>	PVC film, transparent	
<b>Liner:</b>	Silicone paper (70g/m <sup>2</sup> ), blue square print	
<b>Adhesive:</b>	Acrylic	
<b>Adhesion [N/cm]:</b>	1,65	+/- 10 %
<b>Thickness [mm]:</b>	0,08	+/- 5 %

## Standard Dimensions

1.000 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0  
Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.