

## **Product Information**

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



## P.S. FILM

PU plotter cut heat seal material with adhesive polyester backing featuring bright colors. The material grants high washing resistance and an easy cutting, weeding and application. Suitable for multilayer applications.	Average thickness 90 microns
Suitable for cotton, polyester and poly/cotton blends (not suited for treated and dye sublimated textiles)	Suggested cutting settings Blade: 45° Pressure: 90 gf Speed: 30 cm/sec
<ul> <li>Mirror cut the material</li> <li>Weed the exceeding material</li> <li>Place the material on the garment with its polyester backing</li> <li>Heat apply at the conditions shown on the right</li> <li>Remove the carrier warm or cold</li> </ul>	Transfer settings 15 seconds at 150°C (300°F) medium pressure (3-4 bar)
Wait at least <b>24 hours</b> from application before washing. Washing resistance up to <b>80°C</b> , best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.	Washing temperature
The product is certified Öko-Tex® Standard 100 Class I OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100	Ω
2	<ul> <li>featuring bright colors.</li> <li>The material grants high washing resistance and an easy cutting, weeding and application. Suitable for multilayer applications.</li> <li>Fluo colours can leave traces on the support.</li> <li>Suitable for cotton, polyester and poly/cotton blends (not suited for treated and dye sublimated textiles)</li> <li>Mirror cut the material</li> <li>Weed the exceeding material</li> <li>Place the material on the garment with its polyester backing</li> <li>Heat apply at the conditions shown on the right</li> <li>Remove the carrier warm or cold</li> <li>Wait at least 24 hours from application before washing.</li> <li>Washing resistance up to 80°C, best inside-out.</li> <li>Do not use bleach or other aggressive chemical agents.</li> <li>Not suitable for dry cleaning.</li> <li>Suitable for tumble dry, cotton cycle.</li> </ul>

 N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015 ISO 14001:2015

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website <u>www.siser.com</u> For further information, please contact our Sales Office.

MAKE LIVE NOT MAR

Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - <u>www.siser.com</u> r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246